SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

Product ID:	8050-31-5		
Product Name:	RE-390 Rosin Ester		
Revision Date:	Mar 20, 2018	**Date Printed:**	Mar 20, 2018
Version:	1.0	**Supersedes Date:**	N.A.
Manufacturer's Name:	Thames River Chemical Corp.		
Address:	5230 Harvester Road Burlington, ON, CA, L7L 4X4		
Emergency Phone:	CHEMTREC (800) 424-9300		
Information Phone Number:	905-681-5353		
Fax:	905-681-5377		

Product/Recommended Uses: Adhesives, Coatings, Ink

SECTION 2) HAZARDS IDENTIFICATION

Classification

Not classified

Pictograms

None

Signal Word

No signal word available.

Precautionary Statements - General

No precautionary statement available.

Precautionary Statements - Prevention

No precautionary statement available.

Precautionary Statements - Response

No precautionary statement available.

Precautionary Statements - Storage

No precautionary statement available.

Precautionary Statements - Disposal

No precautionary statement available.

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0008050-31-5	Resin acids and Rosin acids, esters with glycerol	100%

SECTION 4) FIRST-AID MEASURES

Inhalation

Move to fresh air. Treat symptomatically.
If symptoms persist, call a physician.

Eye Contact

Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. Get medical attention if symptoms persist. If molten material contacts the eye, immediately flush with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin Contact

Wash with soap and water. Get medical attention if symptoms occur. If burned by contact with hot material, cool molten material adhering to skin as quickly as possible with water, and see a physician for removal of adhering material and treatment of burn. Get medical attention.

Ingestion

Do not induce vomiting. If ingested, seek medical attention immediately.

Most Important Symptoms and Effects, Both Acute and Delayed

No Data Available

Indication of Any Immediate Medical Attention and Special Treatment Needed

No Data Available

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam, water fog, dry chemical, carbon dioxide.

Specific Hazards in Case of Fire

Powdered material may form explosive dust-air mixtures.

Fire-fighting Procedures

Minimize dust generation and accumulation. Isolate immediate hazard area and keep unauthorized personnel out. Do not enter confined fire space without proper protective equipment including self-contained breathing apparatus. See Hazardous Decomposition Products.

Move undamaged containers from immediate hazard area if it can be done safely.

Special Protective Actions

Wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

Isolate hazard area and keep unauthorized personnel away. Stay uphill and/or upstream. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing. Ventilate closed spaces before entering.

Recommended Equipment

Wear chemical protective clothing.

Personal Precautions

Wear safety glasses, rubber gloves, Tyvex type coverall and rubber boots.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Dike far ahead of liquid spill for later disposal.

Methods and Materials for Containment and Cleaning up

Absorb Liquids in vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. Eyewash stations and showers should be available in areas where this material is used and stored All containers must be properly labelled. Avoid contact with molten material. Minimize dust generation and accumulation. Keep container closed.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits.

Storage Room Requirements

Store in dry, cool areas, out of direct sunlight and away from other sources of heat. Empty container retain residue and may be dangerous.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

Wear indirect-vent, impact and splash resistant goggles when working with liquids

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	CANsmg	CANsppm	CANtmg	CANtppm	OSHA STEL (mg/m3)	OSHA STEL (ppm)	OSHA TWA (mg/m3)	OSHA TWA (ppm)	OSHA Carcinogen	OSHA Tables (Z1, Z2, Z3)	OSHA Skin designation	ACGIH STEL (mg/m3)
No applicable chemical	-	-	-	-	-	-	-	-	-	-	-	-

Chemical Name	ACGIH STEL (ppm)	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH TLV Basis	ACGIH Carcinogen	ACGIH Notations
No applicable chemical	-	-	-	-	-	-

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	8.87 lb/gal
Specific Gravity	1.06
Appearance	Solid, pale yellow pastille
Odor Description	rosin-like
pH	N/A
Melting Point	85-95 °C
Low Boiling Point	N/A
High Boiling Point	N/A
Flash Point	N/A
Vapor Pressure	N/A

Vapor Density	N/A
Evaporation Rate	N/A
Water Solubility	N/A

SECTION 10) STABILITY AND REACTIVITY

Reactivity

No Data Available

Stability

Stable under normal storage and handling conditions.

Conditions to Avoid

Avoid dust formation.

Hazardous Reactions/Polymerization

Hazardous polymerization will not occur.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

Carbon Monoxide. Carbon Dioxide.

SECTION 11) TOXICOLOGICAL INFORMATION

Likely Route of Exposure

Inhalation, ingestion, skin absorption

Acute Toxicity

Oral LD-50: (Rat): > 2,000 mg/kg
Dermal LD-50: (Rabbit): > 5,000 mg/kg

Possible mild eye and skin irritant.

Aspiration Hazard

No Data Available

Carcinogenicity

This product is not listed as a carcinogen

No Data Available

Germ Cell Mutagenicity

No Data Available

Reproductive Toxicity

No Data Available

Respiratory/Skin Sensitization

No Data Available

Serious Eye Damage/Irritation

No Data Available

Skin Corrosion/Irritation

No Data Available

Specific Target Organ Toxicity - Repeated Exposure

No Data Available

Specific Target Organ Toxicity - Single Exposure

No Data Available

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

LL50 (Fish, 96 h): > 1,000 mg/l Read-across from a similar material
LL50 (daphnid, 48 h): > 100 mg/l
LL50 (Alga, 72 h): > 1,000 mg/l Read-across from a similar material

Mobility in Soil

No Data Available

Bio-accumulative Potential

No Data Available

Persistence and Degradability

No Data Available

Other Adverse Effects

No Data Available

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, provincial and local laws.

SECTION 14) TRANSPORT INFORMATION

Transport Canada Information

UN number: Not Regulated

Proper shipping name: N/A

Hazard class: N/A

Packaging group: N/A

U.S. DOT Information

UN number: Not Regulated

Proper shipping name: N/A

Hazard class: N/A

Packaging group: N/A

SECTION 15) REGULATORY INFORMATION

Safety, health and environmental regulations

All components of this product are listed on the U.S. TSCA Inventory and listed on the Canadian DSL.

WHMIS: Non-controlled

CAS	Chemical Name	% By Weight	Regulation List
0008050-31-5	Resin acids and Rosin acids, esters with glycerol	100%	DSL,TSCA

SECTION 16) OTHER INFORMATION

Glossary

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CANsmg or CANsppm - Canadian Short Term Exposure Level in mg/L or in ppm; CANtmg or CANtppm - Canadian Time Weighted Average in mg/L or in ppm; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center(US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

Version 1.0:

Revision Date: Mar 20, 2018

First Edition.

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.